



Fábrica de Conductores Eléctricos



FICHA TÉCNICA CABLE SUBTERRÁNEO

Cantidad de conductores x sección nominal	Diametro exterior aproximado	Intensidad de corriente máxima para instalacion en bandejas (Temp. ambiente max. 40 °C)	Resistencia electrica máx. a 20° C en C.C.
mm ²	mm	A	Ohms/km
2 X 1,50	9,50	11	13,30
2 X 2,50	10,60	16	7,98
2 X 4,00	13,00	22	4,95
2 X 6,00	14,00	30	3,30
2 X 10,00	17,00	40	1,91
2 x 16,00	20,00	64	1,45
3 X 1,50	10,00	11	13,30
3 X 2,50	10,80	16	7,98
3 X 4,00	13,50	22	4,95
3 X 6,00	15,80	30	3,30
3 X 10,00	18,00	40	1,91
3 x 16,00	22,00	64	1,45
4 X 1,50	12,00	11	13,30
4 X 2,50	13,00	16	7,98
4 X 4,00	16,30	22	4,95
4 X 6,00	18,00	30	3,30
4 X 10,00	21,00	40	1,91
4 x 16,00	25,00	64	1,45
5 X 1,50	13,80	11	13,30
5 X 2,50	14,50	16	7,98
5 x 4,00	17,30	22	4,95
5 x 6,00	19,20	30	3,30